
Laserliner

VideoFlex HD Micro





This professional video inspection system with compact camera head is perfect for precise visual inspection of small openings, such in pipework, wall cavities and motor vehicles. The high-resolution camera allows extremely detailed images and videos to be captured with 1:1 reproduction on the display with no loss of quality. The sharp digital zoom allows details to be clearly identified. Other benefits are the high-quality LED object lighting, optimum greyscale contrast reproduction, petrol and diesel resistant camera head, and the magnetic stand for setting up the base unit.

TECHNICAL SPECIFICATIONS

3.9 m
CAMERA RESOLUTION 1280

BIELD OF VIEW (FOV) 83°

SCREEN TYPE 5° CO
DISPLAY RESOLUTION 1280

IMAGE FORMAT JPEG

LENGTH OF PROBE 2 m

ILLUMINATION 5 brights incompact of the property o

- Effective problem localisation behind or in objects, walls, pipes, cavities
- Small camera head, ideal for places that are hard to reach
- Very detailed image and video capture using high-resolution camera and 1:1 reproduction on the display with no loss of quality
- Extremely clear digital zoom due to camera's high resolution

TECHNICAL SPECIFICATIONS	
DIAMETER CAMERA HEAD	3.9 mm
CAMERA RESOLUTION	1280 x 720 pixels
FIELD OF VIEW (FOV)	83°
DEPTH OF FOCUS (DOF)	3 8 cm
SCREEN TYPE	5" Colour TFT
DISPLAY RESOLUTION	1280 x 720 pixels
IMAGE FORMAT	JPEG
LENGTH OF PROBE	2 m
ILLUMINATION	5 brightness levels
DIGITAL ZOOM	2x digital zoom in 10%
	increments
MEMORY	Micro-SD memory card up to 32
	GB
PORT	USB
PORTS	USB type C
POWER SOURCE	Li-ion battery pack 7.4V / 2.6Ah /
	19.24Wh
	Power adapter 9V/DC / 2A
DIMENSIONS (W X H X D)	310 mm x 210 mm x 140 mm x
	(incl. holder)
WEIGHT	956 g (incl. battery pack)













< 3 cm +— FOCUS --- > 8 cm



























